

**ABSORBENT ARTICLE COMPRISING
POLYMER WITH LOW GEL INTEGRITY INDEX**

Inventor: Harry J. Chmielewski

Attorney

Christopher C. Campbell
Scott F. Yarnell
Hunton & Williams
1900 K Street, N.W.
Washington, D.C. 20006-1109

09996826 "113001

ABSORBENT ARTICLE COMPRISING POLYMER WITH LOW GEL INTEGRITY INDEX

FIELD OF THE INVENTION

The present invention relates generally to an absorbent composition for absorbent articles such as diapers, incontinence products, training pants, sanitary napkins, and the like. In particular, the present invention is directed to absorbent articles, having unexpectedly superior absorbent properties, comprising an absorbent core disposed between the substantially impermeable backsheet and the permeable topsheet, said absorbent core comprising a polymer having a Gel Integrity Index (GII) of less than about 500 kg mm.

BACKGROUND OF THE INVENTION

Disposable absorbent articles typically include a moisture-impervious backing sheet, an absorbent pad, and a liner sheet that contacts the body of a person wearing the article. In addition, elasticized regions are provided around the edges of the article to secure the article about the waist and legs of a wearer. Diapers typically further comprise opposed front and rear waist portions defining a waist opening, a crotch portion disposed there between, and a pair of elastically contractible leg openings along the side edges of the crotch portion. Disposable diapers having elasticized margins for placement about the legs of a wearer are disclosed in U.S. Patent 4,050,462 and U.S. Patent 5,092,861. An absorbent article having elasticized side margins and waist band margins are shown in U.S. Patent 4,300,562.

Despite previous advancements in the field of absorbent articles, persons of ordinary skill in the art continue their efforts to produce absorbent articles having better absorbency and that are thus are better able to contain urinary and fecal excretions. For instance, problems with prior diaper designs include inferior absorbency and leakage of urinary or fecal material from the article. Prolonged contact of liquid or semi-solid excreta with the skin of the wearer is also a

continuing problem in the art. For example, the moisture vapor and heat generated by the bodily exuded trapped within a diaper may lead conditions adjacent to wearer's skin which promotes skin irritation, infection, and the like. Various approaches to improve the absorbency of absorbent articles have been attempted, including the incorporation of a variety of absorbent composites into said absorbent articles.

Absorbent composites suitable for use in disposable absorbent garments such as diapers, adult incontinent products, feminine care products, training pants, and the like, are known. Generally, such absorbent composites comprise a means of containing a high-absorbency material and a high-absorbency material. Suitable means for containing the high-absorbency material include fibrous matrixes such as those formed from airlaid cellulose fibers or a coform material comprising cellulose fibers and meltblown polyolefin fibers. A wide variety of high-absorbency materials (also known as superabsorbent materials) are known to those skilled in the art.

For example, U.S. Patent No. 5,843,059 to Niemeyer, et al. discloses an absorbent composite suitable for use in disposable absorbent garments and an absorbent garment including such a composite. The composite includes a means for containing a superabsorbent material and a superabsorbent material contained by the containment means. The reference specifies that the superabsorbent material has a Gel Integrity Index of at least about 1500 kg mm. Further, the superabsorbent material is present in the containment means in an amount of from about 10 to about 100 weight percent based on total weight of the containment means and the superabsorbent material.

Disposable absorbent garments formed from absorbent composites are intended to perform many uses. For example, disposable absorbent garments in the form of infant diapers are placed on children and are intended to absorb body fluids for a given period of time. During daytime use, care givers are generally readily available and will often change an infant's diaper

after a single or perhaps two liquid insults. In contrast, the same diaper can be placed on an infant prior to the infant going to bed at night. This diaper may then stay on the infant until morning, a period of eight or more hours. This diaper will be subjected to three, four, or more liquid insults. Thus, a diaper intended for overnight use will have its absorbent ability taxed to a greater extent than a diaper intended for daytime use.

Similarly, cultural differences among different groups of people have been found to produce different diapering habits. That is, some cultural groups tend to change diapers more or less frequently than others. Thus, in certain cultures, even during daytime usage, a diaper may be subjected to three, four, or more liquid insults.

Unfortunately, diapers which perform completely satisfactory in circumstances where they are subjected to one or possibly two liquid insults can perform unsatisfactorily when subjected to three, four, or more liquid insults. This is highly undesirable.

It is possible to design diapers specific for daytime use and diapers specific for nighttime use. Unfortunately, this places a burden on the consumer to maintain proper supplies of both types of diapers. Moreover, it places the added burden on the consumer to time changing the diapers so that an overnight diaper is on the infant when the infant goes to sleep for the night.

Such a solution to the described problem has been found generally unacceptable.

As is apparent from the foregoing, previous approaches present a variety of means for improving absorbency in absorbent garments. However, all of these proposed means are deficient in terms of effectiveness and low product quality, mechanical complexity in design, and/or associated cost inefficiencies.

In view of the deficiencies of the various products and processes disclosed in the above discussed references, it is highly desirable to provide cost-efficient absorbent articles that display superior absorbency, as well as novel compositions and composites for use in said absorbent articles. Further, it is desirable to provide an absorbent composite which is capable of exhibiting

excellent leakage performance in both low loading usage situations and high loading usage situations. It is to this goal that the present invention is directed. Moreover, it is highly desirable to provide a cost-efficient process for producing absorbent articles having superior absorbency.

SUMMARY OF THE INVENTION

5 The present invention provides absorbent articles, and novel compositions and composites for use in same, that display unexpectedly superior absorbency. Further, the present invention provides a cost-efficient process for producing absorbent articles having superior absorbency. Moreover, the present invention provides cost-efficient absorbent articles, methods for preparing and using such articles, and novel compositions and composites for use in same.

10 An embodiment of the present invention provides an absorbent article comprising: a substantially impermeable backsheet; a permeable topsheet; and an absorbent core disposed between the substantially impermeable backsheet and the permeable topsheet, said absorbent core comprising a superabsorbent polymer having a Gel Integrity Index (GII) of less than about 500 kg mm.

15 A further embodiment of the present invention provides an absorbent article comprising: a substantially impermeable backsheet; a permeable topsheet; an absorbent core comprising about 30% to about 50% by weight of a superabsorbent polymer and about 50% to about 70% by weight of wettable fibers, said absorbent core being disposed between the substantially impermeable backsheet and the permeable topsheet, said superabsorbent polymer having a Gel
20 Integrity Index (GII) of less than about 500 kg mm.

An even further embodiment of the present invention provides an absorbent article comprising: a substantially impermeable backsheet; a permeable topsheet; an absorbent core comprising about 30% to about 50% by weight of a crosslinked superabsorbent polymer, said absorbent core being disposed between the substantially impermeable backsheet and the

permeable topsheet, said crosslinked superabsorbent polymer having a Gel Integrity Index (GII) of about 0.10 kg mm to about 0.30 kg mm and an AUL value of less than about 25 g/g.

Sub All A still further embodiment of the present invention provides an absorbent garment comprising: a substantially impermeable backsheet and a permeable topsheet defining a front waste portion and a rear waste portion, said front waste portion and said rear waste portion cooperating to form a waste opening; a crotch region formed between the front waste portion and the rear waste portion; a pair of leg openings on opposed sides of the crotch region; an absorbent core disposed between the substantially impermeable backsheet and the permeable topsheet at the crotch region; wherein the absorbent core comprises a superabsorbent polymer having a Gel Integrity Index (GII) of less than about 500 kg mm.

Another embodiment of the present invention provides a composition comprising: about 10% to about 80% by weight of a superabsorbent polymer, said superabsorbent polymer having a Gel Integrity Index (GII) of less than about 500 kg mm; and about 20% to about 90% by weight of wettable fibers.

Yet another embodiment of the present invention provides a composition prepared by a process comprising: combining about 10% to about 80% by weight of a superabsorbent polymer having a Gel Integrity Index (GII) of less than about 500 kg mm with about 20% to about 90% by weight of wettable fibers.

A further embodiment of the present invention provides a method of preparing a composition for use in absorbent articles comprising: combining wettable fibers with a superabsorbent polymer having a Gel Integrity Index of less than about 500 kg mm; wherein the wettable fibers comprise about 20% to about 90% by weight of the composition and the superabsorbent polymer comprises about 10% to about 80% by weight of the composition.

An even further embodiment of the present invention provides a method of preparing an absorbent article comprising: combining a superabsorbent polymer having a Gel Integrity Index of less than about 500 kg mm with wettable fibers to form an absorbent core and disposing the absorbent core between a substantially impermeable backsheet and a permeable topsheet.

5 **BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1A is perspective view, partially cutaway, of a disposable absorbent diaper according to an implementation of the present invention.

FIG. 1B is a vertical cross-sectional view of a section of the disposable absorbent diaper of FIG. 1A.

10 FIG. 2 illustrates the test probe used in the test method described herein for determining the Gel Integrity Index (GII).

FIG. 3 is a cutaway perspective view of a testing apparatus used to conduct the Fluid Intake Evaluation as described herein.

FIG. 4 is a side elevational view of the apparatus of FIG. 3.

15 **DETAILED DESCRIPTION OF THE INVENTION**

As used herein, “absorbency” refers to the functional capacity and the rate at which absorption occurs as measured by absorption under load (AUL). “Air permeability”, as used herein, refers to the amount of air which the surface permits to pass through during a specified amount of time relative to another surface having the same total area as the first surface.

20 As used herein, the term “absorbent article” refers to articles that absorb and contain exudates, and more specifically refers to articles which are placed against or in proximity to the body of a wearer of the absorbent article to absorb and contain various exudates discharged from the body. A non-exhaustive list of examples of absorbent articles includes diapers, diaper cores, diaper covers, disposable diapers, training pants, feminine hygiene products and adult

25 incontinence products, without limitation.

The term "disposable article" refers to absorbent articles that are intended to be discarded or partially discarded after a single use, i.e., they are not intended to be laundered or otherwise restored or reused. The term "unitary disposable absorbent article" refers to a disposable absorbent article that is essentially a single structure (i.e., it does not require separate manipulative parts such as a diaper cover and insert). As used herein, the term "diaper" refers to an absorbent article generally worn by infants and incontinent persons about the lower torso.

The claims are intended to cover all of the forgoing classes of absorbent articles, without limitation, whether disposable, unitary or otherwise. These classifications are used interchangeably throughout the specification, but are not intended to limit the claimed invention.

The invention will be understood to encompass, without limitation, all classes of absorbent articles, including those described above. The absorbent article and the absorbent core therein may be formed in a variety of ways and the inventions is not intended to be limited to any specific manner of formation. Preferably, the absorbent core is thin in order to improve the comfort and appearance of a garment. The employance of thin, comfortable garments is disclosed, for example without limitation in U.S. Patent No. 5,098,423 to Pineiak et al. which is herein incorporated by reference.

The present invention provides an absorbent article, as well as a method of preparing same and a method of using said absorbent article, having unexpectedly superior properties of absorbency, leakage protection and/or skin wellness. The present invention can be understood by the disclosure herein. The present invention is directed to absorbent articles, having unexpectedly superior absorbency properties. In accordance with an implementation of the present invention, absorbent articles comprise

The absorbent article in accordance with an implementation of the present invention comprises a superabsorbent polymer. Applicants have unexpectedly discovered that superabsorbent polymers having a Gel Integrity Index of less than about 500 kg/mm provide

superior absorbency characteristics. Any superabsorbent polymer having the physical characteristics recited herein are suitable. Persons of skill in the art would readily be able to select and utilize such polymers to implement the present invention, based upon the guidance provided herein. Preferably, the superabsorbent polymer is a polyacrylate.

5 The preparation of such superabsorbent polymers and their incorporation into absorbent articles is described in further detail below and may be accomplished using conventional techniques and methods well known in the art. Persons of ordinary skill in the art would be readily able to prepare and identify superabsorbent polymers meeting these characteristics, without undue experimentation, based upon the guidance provided herein.

10 The present invention is unexpectedly effective with superabsorbent polymers having a low AUL. Preferably, the AUL is less than about 25 g/g at 0.3 psi. As used herein, AUL, refers to measurements at 0.3 psi of grams of a saline per grams polymer. The saline in the AUL measurements herein is a 0.9 % by weight sodium chloride solution. The use of AUL as a measurement of absorbency is well known in the art. A person of ordinary skill in the art would readily understand how to use AUL as a measurement of absorbency, as described herein, in the selection of suitable superabsorbent polymers.

15 Optionally, the polymer is combined with a stabilizing agent. The stabilizing agent is preferably a crosslinking agent. Non-limiting exemplary stabilizing agents include formaldehyde, glutaraldehyde, glyoxal, glyoxylic acid, oxydisuccinic acid, citric acid, a dialdehyde having 2 to 8 carbon atoms, a monoaldehyde having an acid functionality and 2 to 8 carbon atoms, a polycarboxylic acid having 2 to 9 carbon atoms, and combinations thereof. The stabilizing agent is preferably selected from the group consisting of formaldehyde, glutaraldehyde, glyoxal, glyoxylic acid, oxydisuccinic acid, citric acid and combinations thereof. When the stabilizing agent is a crosslinking agent, the crosslinking agent may be selected from the group consisting of a dialdehyde having 2 to 8 carbon atoms, a monoaldehyde having an acid

20

25

functionality and 2 to 8 carbon atoms, a polycarboxylic acid having 2 to 9 carbon atoms, and combinations thereof.

The absorbent core may additionally comprise a surfactant, a filler, an additive or a combination thereof. Preferably, the additive is selected from the group consisting of flame
5 retardants, reinforcing agents, auxiliary blowing agents, medicaments, fragrances, colorants, cleaners, abrasives and combinations thereof.

The absorbent article may be, for example, a diaper, incontinent brief, training pant, diaper holder, diaper liner, sanitary napkin, hygienic garment or combinations thereof. Diapers may include daytime diapers, nighttime diapers, long-term wear diapers, travel diapers,
10 swimming diapers, daytime/nighttime diapers, male diapers, female diapers, unisex diapers, active diapers, seasonal diapers, cold weather diapers, warm weather diapers, medicated diapers or combinations thereof.

The physical characteristics of the superabsorbent polymer in accordance with an implementation of the present invention are determined by various factors. These factors also
15 influence the cost effectiveness of the absorbent articles. While a wide variety of superabsorbent materials are known, the present invention relates, in one aspect, to the proper selection of a superabsorbent material to allow formation of improved absorbent composites and disposable absorbent garments. U.S. Patent No. 5,147,343 issued to Kellenberger, U.S. Patent No. 4,673,402 issued to Weisman, U.S. Patent No. 5,281,207 issued to Chmielewski et al., and U.S.
20 Patent No. 4,834,735 issued to Alemany, et al. disclose many types of polymers and methods for making them, and are incorporated herein by reference for all purposes and in a manner that is consistent herewith. Superabsorbent polymers and methods of making them are described in U.S. Patent Nos. 4,666,983 and 4,734,478 issued to Tsubakimoto et al. which are incorporated herein by reference for all purposes and. in a manner that is consistent herewith. Also, U.S.

25 Patent No. 5,281,207 to Chmielewski, et al. generally discloses methods and materials for

making an absorbent article and is also incorporated herein by reference for all purposes and in a manner that is consistent herewith.

Applicants have discovered that the performance of a superabsorbent material in absorbent composites intended for overnight usage or other usage situations, in which the absorbent composites will be subjected to high levels of liquid loading, depends, at least in part, on the gel characteristics of the superabsorbent material contained in the composite. As used herein, the gel characteristics of a superabsorbent material refers to the Gel Integrity Index herein described in greater detail in connection with the examples. Stated generally, the Gel Integrity Index is a measure of the resistance to flow as measured by penetration resistance of the gel slurry formed when the superabsorbent material is subjected to a high level of liquid loading.

Specifically, the Gel Integrity Index measures the resistance to penetration of the gel slurry formed by allowing a superabsorbent material to free swell in an aqueous solution containing 0.9 weight percent sodium chloride in which the superabsorbent material and sodium chloride solution are present in a weight ratio of 1:50. The Gel Integrity Index is measured as follows. First, mix one part by weight of superabsorbent material having a moisture content of less than 10 weight percent and 50 parts of an aqueous solution containing 0.9 weight percent sodium chloride, in a container having a 33 millimeter diameter and a height of 62 millimeters. Secondly, allow the superabsorbent material to swell for at least one hour until it appears to have generally reached equilibrium. Thirdly, measure the resistance of a sample of the mixture of swollen superabsorbent and aqueous solution of sodium chloride to penetration to a test probe, by attaching a clear anodized aluminum test probe having a 1.27 centimeter diameter, a length of 11.43 centimeters, and a rounded end having a 6.35 millimeter radius, to descend downward from a load cell capable of determining the load exerted on the load cell by the test probe; raising the sample of the mixture of swollen superabsorbent and aqueous solution of sodium chloride to the rounded end of the probe until a load greater than 0.1 gram but less than one gram is exerted

on the load cell; lowering the test probe into the sample, for a distance of 40 millimeters at a constant speed of 16 inches per minute; and determining the resistance of the sample to the introduction of the test probe into the sample, as the probe penetrates from 15 to 40 millimeters into the sample. If the superabsorbent is in particulate form, the particles should preferably be

5. screened to have a maximum cross-sectional diameter within the range of from about 50 microns to about 1000 microns, more preferably from about 100 microns to about 800 microns.

10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044 1045 1046 1047 1048 1049 1050 1051 1052 1053 1054 1055 1056 1057 1058 1059 1060 1061 1062 1063 1064 1065 1066 1067 1068 1069 1070 1071 1072 1073 1074 1075 1076 1077 1078 1079 1080 1081 1082 1083 1084 1085 1086 1087 1088 1089 1090 1091 1092 1093 1094 1095 1096 1097 1098 1099 1100 1101 1102 1103 1104 1105 1106 1107 1108 1109 1110 1111 1112 1113 1114 1115 1116 1117 1118 1119 1120 1121 1122 1123 1124 1125 1126 1127 1128 1129 1130 1131 1132 1133 1134 1135 1136 1137 1138 1139 1140 1141 1142 1143 1144 1145 1146 1147 1148 1149 1150 1151 1152 1153 1154 1155 1156 1157 1158 1159 1160 1161 1162 1163 1164 1165 1166 1167 1168 1169 1170 1171 1172 1173 1174 1175 1176 1177 1178 1179 1180 1181 1182 1183 1184 1185 1186 1187 1188 1189 1190 1191 1192 1193 1194 1195 1196 1197 1198 1199 1200 1201 1202 1203 1204 1205 1206 1207 1208 1209 1210 1211 1212 1213 1214 1215 1216 1217 1218 1219 1220 1221 1222 1223 1224 1225 1226 1227 1228 1229 1230 1231 1232 1233 1234 1235 1236 1237 1238 1239 1240 1241 1242 1243 1244 1245 1246 1247 1248 1249 1250 1251 1252 1253 1254 1255 1256 1257 1258 1259 1260 1261 1262 1263 1264 1265 1266 1267 1268 1269 1270 1271 1272 1273 1274 1275 1276 1277 1278 1279 1280 1281 1282 1283 1284 1285 1286 1287 1288 1289 1290 1291 1292 1293 1294 1295 1296 1297 1298 1299 1300 1301 1302 1303 1304 1305 1306 1307 1308 1309 1310 1311 1312 1313 1314 1315 1316 1317 1318 1319 1320 1321 1322 1323 1324 1325 1326 1327 1328 1329 1330 1331 1332 1333 1334 1335 1336 1337 1338 1339 1340 1341 1342 1343 1344 1345 1346 1347 1348 1349 1350 1351 1352 1353 1354 1355 1356 1357 1358 1359 1360 1361 1362 1363 1364 1365 1366 1367 1368 1369 1370 1371 1372 1373 1374 1375 1376 1377 1378 1379 1380 1381 1382 1383 1384 1385 1386 1387 1388 1389 1390 1391 1392 1393 1394 1395 1396 1397 1398 1399 1400 1401 1402 1403 1404 1405 1406 1407 1408 1409 1410 1411 1412 1413 1414 1415 1416 1417 1418 1419 1420 1421 1422 1423 1424 1425 1426 1427 1428 1429 1430 1431 1432 1433 1434 1435 1436 1437 1438 1439 1440 1441 1442 1443 1444 1445 1446 1447 1448 1449 1450 1451 1452 1453 1454 1455 1456 1457 1458 1459 1460 1461 1462 1463 1464 1465 1466 1467 1468 1469 1470 1471 1472 1473 1474 1475 1476 1477 1478 1479 1480 1481 1482 1483 1484 1485 1486 1487 1488 1489 1490 1491 1492 1493 1494 1495 1496 1497 1498 1499 1500 1501 1502 1503 1504 1505 1506 1507 1508 1509 1510 1511 1512 1513 1514 1515 1516 1517 1518 1519 1520 1521 1522 1523 1524 1525 1526 1527 1528 1529 1530 1531 1532 1533 1534 1535 1536 1537 1538 1539 1540 1541 1542 1543 1544 1545 1546 1547 1548 1549 1550 1551 1552 1553 1554 1555 1556 1557 1558 1559 1560 1561 1562 1563 1564 1565 1566 1567 1568 1569 1570 1571 1572 1573 1574 1575 1576 1577 1578 1579 1580 1581 1582 1583 1584 1585 1586 1587 1588 1589 1590 1591 1592 1593 1594 1595 1596 1597 1598 1599 1600 1601 1602 1603 1604 1605 1606 1607 1608 1609 1610 1611 1612 1613 1614 1615 1616 1617 1618 1619 1620 1621 1622 1623 1624 1625 1626 1627 1628 1629 1630 1631 1632 1633 1634 1635 1636 1637 1638 1639 1640 1641 1642 1643 1644 1645 1646 1647 1648 1649 1650 1651 1652 1653 1654 1655 1656 1657 1658 1659 1660 1661 1662 1663 1664 1665 1666 1667 1668 1669 1670 1671 1672 1673 1674 1675 1676 1677 1678 1679 1680 1681 1682 1683 1684 1685 1686 1687 1688 1689 1690 1691 1692 1693 1694 1695 1696 1697 1698 1699 1700 1701 1702 1703 1704 1705 1706 1707 1708 1709 1710 1711 1712 1713 1714 1715 1716 1717 1718 1719 1720 1721 1722 1723 1724 1725 1726 1727 1728 1729 1730 1731 1732 1733 1734 1735 1736 1737 1738 1739 1740 1741 1742 1743 1744 1745 1746 1747 1748 1749 1750 1751 1752 1753 1754 1755 1756 1757 1758 1759 1760 1761 1762 1763 1764 1765 1766 1767 1768 1769 1770 1771 1772 1773 1774 1775 1776 1777 1778 1779 1780 1781 1782 1783 1784 1785 1786 1787 1788 1789 1790 1791 1792 1793 1794 1795 1796 1797 1798 1799 1800 1801 1802 1803 1804 1805 1806 1807 1808 1809 1810 1811 1812 1813 1814 1815 1816 1817 1818 1819 1820 1821 1822 1823 1824 1825 1826 1827 1828 1829 1830 1831 1832 1833 1834 1835 1836 1837 1838 1839 1840 1841 1842 1843 1844 1845 1846 1847 1848 1849 1850 1851 1852 1853 1854 1855 1856 1857 1858 1859 1860 1861 1862 1863 1864 1865 1866 1867 1868 1869 1870 1871 1872 1873 1874 1875 1876 1877 1878 1879 1880 1881 1882 1883 1884 1885 1886 1887 1888 1889 1890 1891 1892 1893 1894 1895 1896 1897 1898 1899 1900 1901 1902 1903 1904 1905 1906 1907 1908 1909 1910 1911 1912 1913 1914 1915 1916 1917 1918 1919 1920 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 264

Alternatively, the containment means may comprise two layers of material which are joined together to form a pocket or compartment, more particularly, a plurality of pockets, which pockets contain a superabsorbent material. In such a case, at least one of the layers of material should be water pervious. The second layer of material may be water pervious or water impervious. The layers of material may be clothlike woven or nonwovens, closed- or open-celled foams, perforated films, elastomeric materials, or may be fibrous webs of material. When the containment means comprises layers of material, the material should have a pore structure small enough or tortuous enough to contain the majority of superabsorbent material. The containment means may also comprise a laminate of two layers of material between which the superabsorbent material is located and contained.

Further, the absorbent article may comprise a fibrous matrix of wettable fibers wherein the superabsorbent polymer is disbursed. The superabsorbent polymer may be uniformly or unevenly disbursed. Moreover, the disbursement of the superabsorbent polymer may be targeted to attain optimal characteristics. The superabsorbent polymer may be non-affixed or affixed directly or indirectly to the fibrous matrix.

Any suitable amount of superabsorbent polymer may comprise the absorbent core. A person of skill in the art would readily be able to determine such a suitable amount without undue experimentation. Preferably, the superabsorbent polymer is about 10% to about 80% by weight of the absorbent core. More preferably, the superabsorbent polymer is about 20% to about 60% by weight of the absorbent core. Even more preferably, the superabsorbent polymer is about 30% to about 50% by weight of the absorbent core.

The absorbent core may further comprises wettable fibers. Any suitable amount of wettable fibers may comprise the absorbent core. A person of skill in the art would readily be able to determine such a suitable amount without undue experimentation. Preferably, the

absorbent core additionally comprises about 20% to about 90% of wettable fibers. More preferably, the absorbent core additionally comprises about 50% to about 70% by weight of wettable fibers.

Any fibers capable of forming a containment means capable of containing a superabsorbent material and of forming a composite when in combination with the superabsorbent material are believed suitable for use in the present invention. It is often preferred that the fibers are hydrophilic. As used herein, a fiber will be considered to be "hydrophilic" when it possesses a contact angle of water in air of less than 90 degrees. For the purposes of this application, contact angle measurements are determined as set forth by Good and Stromberg in "Surface and Colloid Science," Volume 11 (Plenum Press, 1979).

Fibers suitable for use in the present invention include cellulosic fibers such as wood pulp fluff, cotton, cotton linters, rayon, cellulose acetate, and the like, as well as synthetic polymeric fibers. The synthetic polymeric fibers may be formed from inherently hydrophilic polymeric materials or may be formed from inherently hydrophobic polymeric materials (water in air contact angle of greater than 90 degrees), which fibers are then treated to render at least the outer surface of the fibers hydrophilic. For example, hydrophilic fibers may be formed from an intrinsically hydrophilic polymer such as a block copolymer of nylon, e.g., nylon-6, and a polyethylene oxide diamine. Such block copolymers are commercially available from Allied Signal Inc. under the trade designation HYDROFIL™. Alternatively, the fibers may be formed from an intrinsically hydrophobic polymer such as polyolefin or polyester which has been surface modified to provide a generally nonfugitive hydrophilic surface.

When the hydrophilic fibers are formed by applying a hydrophilic surface treatment to a generally hydrophobic polymer, it is believed desirable to employ a generally nonfugitive surface treatment in order to obtain the desired performance standards. Absorbent structures employed in absorbent garments such as diapers are, as discussed above, often subjected to multiple liquid

insults. If the surface treatment is fugitive, it may be washed off with the initial insult, thus, exposing the hydrophobic fiber surface. The hydrophobic fiber surface may impede the absorption performance of the absorbent structure. Of course, there are instances where hydrophobic fibers may be employed depending in part on the fluid to be absorbed.

5 The synthetic polymeric fibers suitable for use in the present invention may suitably be formed through a melt-extrusion process wherein fibers of a polymeric material are extruded and attenuated to produce fibers having a desired diameter. Alternatively the fibers may be formed through a spinning process. Any fiber-producing process known to those skilled in the art is believed to be suitable for use in the present invention.

10 Fibers suitable for use in the present invention generally have a length of at least about 1 millimeter. The fibers may have a maximum length approaching infinity. That is to say, the fibers may be essentially continuous, such as those fibers formed through a meltblowing process under certain conditions known to those skilled in the art.

15 Reference to a "mixture" is intended to refer to a combination of fibers and superabsorbent material in which the superabsorbent material is in direct contact with the fibers or is not substantially prevented from migrating into contact with the fibers. Thus, for example, in a multi-layered absorbent core in which the first layer comprises an airlaid mixture of wood pulp fluff and superabsorbent material and the second layer comprises only airlaid fluff, only the first layer is considered a "mixture" provided substantial dry migration of the superabsorbent material between the two layers is prevented. Methods of preventing such migration are known and include separating the layers by a tissue wrapsheet, high density fiber layer, or similar means to prevent substantial dry migration of the superabsorbent material between the two layers. The mixture of superabsorbent materials and fibers may be relatively homogenous or relatively nonhomogeneous. In the case of a nonhomogeneous mixture, the superabsorbent may be
25 arranged in a gradient or may be layered with the fibers.

When the containment means comprises a mixture of fibers and a superabsorbent material, the mixture of fibers and the superabsorbent material may be formed in a wide variety of ways. For example, the mixture may be formed by air laying or wet laying the fibers in the superabsorbent material, according to processes known in the art, to form batts of the mixture. Air laying the mixture of fibers and superabsorbent material is intended to encompass both the situation wherein preformed fibers are air laid with the superabsorbent material as well as the situation in which the superabsorbent material is mixed with the fibers as the fibers are being formed, such as through a meltblowing process.

The absorbent composites according to the present invention are suited to absorb many fluids, including body fluids such as urine, menses, and blood; and are suited for use in absorbent garments such as diapers, adult incontinent products, bed pads, and the like; in catamenial devices such as sanitary napkins, tampons, and the like; and in other absorbent products such as wipes, bibs, wound dressings, food packaging and the like. Accordingly, in another aspect, the present invention relates to a disposable absorbent garment comprising an absorbent composite as described above. A wide variety of absorbent garments are known to those skilled in the art.

The absorbent composites of the present invention can be incorporated into such known absorbent garments. Exemplary absorbent garments are generally described in U.S. Pat. Nos. 4,710,187 issued Dec. 1, 1987, to Boland et al.; 4,762,521 issued Aug. 9, 1988, to Roessler et al.; 4,770,656 issued Sep. 13, 1988, to Proxmire et al.; 4,798,603 issued Jan. 17, 1989, to Meyer et al.; 5,411,497 issued May 2, 1995 to Tanzer et al.; 5,433,715 issued Jul. 18, 1995 to Tanzer et al.; 5,425,725 issued Jun. 20, 1995 to Tanzer et al.; and commonly assigned U.S. patent application Ser. No. 08/096,654, now U.S. Pat. No. 5,509,915 filed Jul. 22, 1993, as a continuation of Ser. No. 07/757,760, filed Sep. 11, 1991, and now abandoned in the name of Hanson et al. (EP 0 539 703) and Ser. No. 08/369,558 now U.S. Pat. No. 5,593,399 filed Jan. 6, 1995, as a continuation

of Ser. No. 145,926, filed Oct. 29, 1993 in the name of Tanzer et al., all of which are incorporated herein by reference. As a general rule, the absorbent disposable garments according to the present invention comprise a bodyside liner adapted to contact the skin of a wearer, an outer cover superimposed in facing relation with said liner, and an absorbent composite, such as those described above, superimposed on said outer cover and located between the bodyside liner and the outer cover. Those skilled in the art will recognize materials suitable for use as the bodyside liner and outer cover. Examples of materials suitable for use as the bodyside liner are hydrophilized spunbond polypropylene or polyethylene with a basis weight of from about 15 to about 25 grams per square meter, and the like. Examples of materials suitable for use as the outer cover are water-impervious materials such as polyolefin films, as well as water-pervious or water vapor-pervious materials.

The present invention also provides improved disposable absorbent articles such as but not limited to diapers, sanitary napkins that incorporate the absorbent composite of the present invention. Disposable diaper articles are described in U.S. Patent Nos. 4,673,402; 5,147,343; 5,330,822; 4,834,735; and 5,281,207, which are incorporated herein by reference for all purposes. A preferred disposable diaper, for the purpose of this invention, is shown in FIGS. 1A and 1B. In accordance with FIGS. 1A and 1B, a disposable diaper **10** comprises a liquid impermeable backsheet **12**, a liquid permeable topsheet **14** and an absorbent core **16** positioned between the topsheet **14** and the backsheet **12**.

In accordance with an implementation of the present invention, in at least a layer of the absorbent core, in a target region thereof indicated by circle **21'**, taken in the Z-direction thereof (i.e., in a direction from top to bottom, away from the wearer), the superabsorbent material comprises a substantially continuous phase. For purposes of this disclosure, the substantially continuous phase is provided wherein a sufficient quantity of particles of the superabsorbent material are in multiple point contact with each other, both prior to absorption of liquid and

thereafter, to thereby define a capillary network for facilitating liquid transport within the core structure. A sufficiently quantity of wood pulp fibers are intermixed with the superabsorbent material in the continuous phase. This quantity of wood pulp fiber acts to maintain the stability of the absorbent structure by integrating the region of the continuous phase of superabsorbent particles with adjacent portions of the absorbent structure.

As shown in the cross-sectional view FIG. 1B, the layer of the absorbent core having the continuous phase portion **21'** is preferably positioned between two layers, designated **22'**, each comprising predominantly wood pulp fibers. In the case of a diaper, the liquid permeable top sheet **14** allows urine to flow through the sheet to the absorbent core **16** and also keeps the baby from directly contacting the absorbent panel structure. This configuration provides more comfort for the baby and also helps to position the absorbent panel structure. Liquid permeable top sheets, and liquid impermeable back sheets, are well known to those skilled in the art, and these components can be suitably selected in practicing the present invention.

Backsheet **12** is impermeable to liquids, and thus, helps to retain a liquid so that the liquid may be absorbed and retained by the absorbent panel structure. In a baby diaper, the impermeable back sheet is typically a sheet of plastic film, such as polyethylene, that helps to retain the urine so that the urine may be absorbed by the absorbent panel structure of the diaper. For a detailed discussion of materials that can be used in the top and back sheet of a diaper, see U.S. Patent No. 5,281,207 issued to Chmielewski, et al. and which is incorporated herein for all purposes.

The absorbent core **16** is optionally made of a two phase matrix comprising wood pulp fiber and surface crosslinked polymeric superabsorbent material. As noted above, by two phase, it is meant that the absorbent core has two components, fibers (preferably wood pulp) and a superabsorbent material. The absorbent structure may comprise more than one layer. For example, the absorbent structure may have a layer that is substantially wood pulp fiber, while on

top of this layer the absorbent structure may have another layer of wood pulp fiber that contains particulate superabsorbent material dispersed in the wood pulp fiber. It is contemplated that many different combinations of layers may be used in the practice of the present invention. For example, in a preferred embodiment of the invention, in at least the target region **20**, a three layer system is formed in which a layer containing superabsorbent particulate material in a substantially continuous phase is positioned between adjacent layers formed predominantly of wood pulp fiber.

Because superabsorbent material is one of the most costly components of an absorbent structure, efficient use and positioning of the material is beneficial. Specific positioning of the superabsorbent material in areas most likely to be insulted with urine allows for the most cost effective utilization of this component. Specific positioning of superabsorbent material can be accomplished through any of several methods, such as by the method and apparatus as described and claimed in U.S. Patent 5,279,854, which is incorporated herein by reference.

Persons of ordinary skill in the art would readily be able to use a variety of conventional techniques to produce superabsorbent polymers having the Gel Integrity Index characteristics disclosed herein, in accordance with an implementation of the present invention. Persons of ordinary skill in the art would be readily able to vary other characteristics discussed herein to obtain the superabsorbent polymers in accordance with the present invention, using conventional materials and techniques. Further, various techniques and methods for measuring such characteristics are well known in the art.

Absorbent cores having suitable superabsorbent polymeric composition and the structural features hereinbefore described will, in general, possess mechanical properties, e.g., resistance to compression deflection, flexibility, recovery from compression deflection, integrity, softness, etc., which render such materials suitable for use as absorbent structures in absorbent articles such as disposable diapers. Within the aforementioned structural limitations, however, it is

possible to select certain combinations of parameters and/or certain preparation techniques and conditions which provide absorbents that exhibit especially desirable mechanical properties.

Thus, the superabsorbent polymer of the preferred structures herein will possess both viscous, i.e., fluid-like, properties and elastic, i.e., spring-like, properties. It is important that the superabsorbent polymeric material which forms the structure have physical, rheological, and morphological attributes which, under conditions of use, impart suitable flexibility, resistance to compression deflection, and dimensional stability to the absorbent composition material.

The superabsorbent polymers of the present invention can be prepared using any suitable polymerization and post-polymerization process steps and using any suitable combination of monomeric materials, so long as superabsorbent polymers result which have the hereinbefore described essential, and if desired preferred, structural and mechanical characteristics.

The absorbent core of the absorbent article embodiments of this invention can consist solely of one or more of the composition structures herein. For example, the absorbent core may comprise a single unitary piece of composition shaped as desired or needed to best fit the type of absorbent article in which it is to be used. Alternatively, the absorbent core may comprise a plurality of composition pieces or particles which may be adhesively bonded together or which may simply be constrained into an unbonded aggregate held together by an overwrapping of envelope tissue or by means of the topsheet and backing sheet of the absorbent article.

The absorbent core of the absorbent articles herein can also comprise other, e.g., conventional, elements or materials in addition to one or more absorbent structures of the present invention. For example, absorbent articles herein may utilize an absorbent core which comprises a combination, e.g., an airlaid mixture, of particles or pieces of the absorbent structures herein and conventional absorbent materials such as a) wood pulp or other cellulosic fibers, and/or, b) particles or fibers of polymeric gelling agents.

In one embodiment involving a combination of the absorbent material herein and other

absorbent materials, the absorbent articles herein may employ a multi-layer absorbent core configuration wherein a core layer containing one or more structures of this invention may be used in combination with one or more additional separate core layers comprising conventional absorbent structures or materials. Such conventional absorbent structures or materials, for example, can include air-laid or wet-laid webs of wood pulp or other cellulosic fibers. Such conventional structures may also comprise conventional absorbent compositions.

As indicated hereinbefore, the fluid handling and mechanical characteristics of the specific absorbent structures herein render such structures especially suitable for use in absorbent articles in the form of disposable diapers. Disposable diapers comprising the absorbent structures of the present invention may be made by using conventional diaper making techniques, but by replacing or supplementing the pulp fibers or modified cellulosic core absorbents typically used in conventional diapers with one or more structures of the present invention. Absorbent structures of this invention may thus be used in diapers in single layer or, as noted hereinbefore, in various multiple layer core configurations.

Another preferred type of absorbent article which can utilize the absorbent structures of the present invention comprises form-fitting products such as training pants. Such form-fitting articles will generally include a nonwoven, flexible substrate fashioned into a chassis in the form of briefs or shorts. An absorbent structure according to the present invention can then be affixed in the crotch area of such a chassis in order to serve as an absorbent "core". This absorbent core will frequently be over-wrapped with envelope tissue or other liquid pervious, nonwoven material. Such core overwrapping thus serves as the topsheet for the form-fitting absorbent article.

Due to the wide variety of materials which may be incorporated into the absorbent articles of the present invention, the present invention is not intended to be limited to any specific materials. The topsheet, backsheet, absorbent core and other components of the absorbent

articles in accordance with various implementations of the present invention may comprise various materials. Persons of ordinary skill in the art would be readily able to select appropriate materials for use in the various components of the present invention based upon the materials.

In accordance with various implementations of the present invention, the absorbent core

5 may contain one or more wettable fibers, one or more polymers or combinations thereof. Non-

limiting exemplary fibers which may be used in the articles of the present invention include,

without limitation, cellulose fibers, cellulose acetate fibers, rayon fibers, Courtauld's LYOCCEL

fibers, polyacrylonitrile fibers, surface modified (hydrophilic) polyester fibers, surface modified

polyolophin/polyester bicomponent fibers, surface modified polyester/polyester bicomponent

10 fibers, cotton fibers or blends thereof. Preferably cellulose acetate, rayon, Courtauld's LYOCCEL,

polyacrylonitrile, cotton fibers and cotton linters or combinations thereof are used in the process

of the present invention. More preferably, cellulose fibers are used as the fiber material in the

present invention.

Other materials may be added to the fiber or pulp material which is optionally processed

15 in a fiberizing apparatus, such as a hammermill. The additives may be added at any point in the

process. Non-limiting exemplary additives which may be incorporated into the process of the

present invention include a polymer such as a superabsorbent polymer, hydrophilic polymers,

potato starch, corn starch, wheat starch or rice starch, or combinations thereof. Various different

combinations of materials may be used as are known to persons of ordinary skill in the art and

20 which are described in U.S. Patent No. 6,068,620 which is herein incorporated by reference.

Preferably, the mixtures incorporated in the invention are substantially homogenous mixtures or

uniformly distributed mixtures. Absorbent articles in accordance with an implementation of the

present invention are prepared using conventional methods and materials well known to persons

of ordinary skill in the art, using the guidelines provided herein.

3 } The test method for determining the Gel Integrity Index of the superabsorbent polymer in accordance with the present invention is provided in U.S. Patent No. 5,843,050, issued on December 1, 1998 to Niemeyer et al., which is incorporated herein by reference in its entirety.

5 TEST METHODS

Moisture Content of Superabsorbent Material:

The following test method is suitably used to determine the moisture content of superabsorbent material.

Equipment Used:

1. An electronic balance accurate to 0.001 gram, such as that available from Sartorius Co. under the trade designation BP310S.

2. A forced-air oven capable of maintaining an internal temperature of 105 degrees C plus or minus 2 degrees C. Such an oven is commercially available from Blue M under the designation Stabil-Therm.

3. A desiccator containing fresh calcium chloride. Such a desiccator can be obtained from Baxter Scientific Co. under the designation Pyrex Knob Top Desiccator.

4. A 60 millimeter aluminum weighing dish, such as that available from Sargent Welch Co. under the designation #S 25725.

Test Procedure:

1. Preheat oven to 105 degrees C plus or minus 2 degrees C.

5

2. Weigh the aluminum weighing dish and record the weight as W1.

3. Place 8-10 grams of superabsorbent material in the weighing dish.

10

4. Weigh the weighing dish and superabsorbent material and record the weight as W2.

5. Place the weighing dish and superabsorbent material in the preheated oven for 3 hours.

6. Remove the weighing dish and superabsorbent material from the oven and place in desiccator.

15

Allow to cool for approximately 30 minutes.

7. Remove the weighing dish and superabsorbent material from the desiccator and immediately weigh the cooled weighing dish and superabsorbent material. Record the weight as W3.

20

8. The percent moisture is calculated by the formula:

$$\% \text{ moisture} = 100 \times (W2 - W3) / (W2 - W1)$$

Gel Integrity Index :

25

The following test method is used for determining the Gel Integrity Index (GII) of superabsorbent polymers in accordance with the present invention.

Equipment Used

5

1. An electronic balance accurate to 0.001 gram, such as that available from Sartorius Co. under the trade designation BP310S.

2. U.S. Standard 30 mesh and 50 mesh screens, automatic sieve shaker, such as a Ro-Tap Sieve Shaker commercially available from Baxter Scientific.

10

3. Air tight glass containers, such as those available from Baxter Scientific under the trade designation Qorpak Bottles AP-2103.

15

4. 0.87 percent aqueous saline solution commercially available from Baxter Scientific under the trade designation Blood Bank Saline.

5. A 33 millimeter diameter by 62 millimeter high, 55 milliliter capacity polystyrene vial, such as that commercially available from Baxter Scientific under the trade designation Continental

20

Glass and Plastic Co. Polystyrene Snap Cap Vial.

6. A Tensile Tester, such as that commercially available from Instron under the trade designation Model #1122. The Tensile Tester is interfaced with a personal computer including Windows.TM. and Test Works.TM. for Windows software.

25

7. A 2000 gram compression load cell for the Tensile Tester of No. 6, which load cell is commercially available from Instron.

8. Test Works.TM, software commercially available from Sintech under the trade designation

5 Test Works for Windows.

9. A 1.27 centimeter diameter (d) clear anodized aluminum test probe as illustrated in FIG. 2.

With reference to FIG. 2, the test probe 50 has a length A of 11.43 centimeters. The test probe 50

has a threaded portion 52 having a length B of 1 centimeter. The threaded portion 52 is adapted

10 to screw into the load cell of number 7 above. The end of probe 50 opposite threaded portion 52 is rounded (0.635 centimeter radius).

10. A laboratory jack

15 11. Polystyrene weigh boat, commercially available from Baxter Scientific under the trade designation S/P Brand dispo Weigh Boat Containers.

Sample Preparation:

20 1. Take a quantity of superabsorbent material as it is received from the superabsorbent supplier, but having a moisture content of less than 10 weight percent, and prescreen according to ASTM Test Method D-1921. If the superabsorbent material has a moisture content of greater than 10 weight percent, it should be dried at about 105 degrees C. until it has a moisture content of less than 10 weight percent. Fibrous superabsorbent materials do not need to be prescreened but
25 should have (or be dried to) a moisture content of less than 10 weight percent. Transfer the

superabsorbent material passing through the U.S. Standard 30 mesh screen and retained on the U.S. Standard 50 mesh screen (300-600 micron portion) of the superabsorbent material into the air tight container to prevent moisture pick-up.

- 5 2. Transfer 40 milliliters (+0.01 milliliter) of the 0.87 percent Baxter Blood Bank saline into the polystyrene vial.
3. Measure 0.80 gram of the superabsorbent material obtained under No. 1 above (300-600 micron particle size) into the polystyrene weigh boat. Transfer the superabsorbent material from the weigh boat into the polystyrene vial, place the cap on the vial, and swirl gently for 10 seconds. After swirling, allow the superabsorbent material to swell undisturbed at room temperature for one to eight hours. The superabsorbent is allowed to swell until it appears to have generally reached equilibrium (has stopped swelling). One hour is generally sufficient to reach this apparent equilibrium stage. Transfer the vial with as little movement as possible to the platform of the tensile tester. Triplicate samples for each superabsorbent material to be tested are prepared.

Test Set-Up:

- 20 1. Plug the 2000 gram compression load cell into the tensile tester and allow it to warm up for at least 30 minutes.
2. Turn on the personal computer and enter the Windows.TM program.
- 25 3. Enter the TestworksTM software.

4. Set the parameters in the compression master preset program as provided in U.S. Patent No. 5,843,059 incorporated herein:

5. Calibrate the load cell to within 1 percent according to the calibration procedure supplied with the Tensile Tester.

6. Once calibrated, mount the load cell to the Tensile Tester frame and attach the 1.27 centimeter diameter test probe to the load cell.

Test Procedure:

1. Click on "sample" at the top of the screen and type in a sample description. Press enter.

2. Zero the load on the load cell.

3. Remove the cap from one of the polystyrene vials containing the swollen superabsorbent material prepared as described above and place it on a laboratory jack located below the test probe which has been securely screwed into the load cell.

4. Raise the sample with the laboratory jack until a load greater than 0.1 g but less than 1 g is exerted on the load cell.

5. Re-zero the load on the load cell and then click on "run" at the top of the screen.

6. The Instron machine will then lower the 1.27 centimeter diameter test probe into the sample for a distance of 40 mm at a constant speed of 16 inches per minute.

7. When the probe stops, press "return" on the Instron panel and raise the probe from the sample.

5 Wipe off the probe. Test the remaining two samples of the same material in the manner described above.

Print the results of the testing. The Gel Integrity Index is the area under the curve generated by the Tensile Tester equipment from initiation of the test procedure to the end of the procedure for the three test samples. The value is reported as the average energy of the three replications in kg mm.

Fluid Intake Evaluation:

15 FIGS. 3 and 4 illustrate the test apparatus used to conduct the fluid intake evaluation.

With reference to FIG. 3, a 4 inch x 10 inch test sample (shown in phantom at 60) is provided.

The test sample 60 is placed flat and smooth under a cylinder plate assembly 62 such that the cylinder 64, which has a 5.1 centimeter internal diameter, is positioned over the center 66 of lower plate 68 and raised platform 70. Plate 62 and 68 are 14 inches long and 8 inches wide and are formed from a material such as Plexiglas. Raised platform 70 is 1/2 inch high (d) by 6 inches long (e) by 3 inches wide (f). The cylinder 64 extends a distance (g) of about 1/32 inch below the cylinder plate assembly 62. This can be seen by reference to FIG. 4. Funnel 72 is sized to fit in cylinder 64 and has a receiving end which is 7 centimeters in diameter and an exit end which is 1.2 centimeters in diameter.

The fluid intake evaluation is performed as follows. The 4 inch by 10 inch test sample 60 is positioned over raised platform 70 such that it is centered thereon. Two 3 inch by 11 inch strips of blotter paper are provided. The blotter paper is 100 pound blotter paper commercially available from James River Corporation under the trade designation 100 pound Verigood Blotter Paper. Each blotter paper strip is weighed and its weight recorded. One strip of blotter paper is placed immediately adjacent, but not touching, each longitudinal side (10 inch) of the test sample 60. Cylinder plate assembly 62 is placed on top of lower plate 68 such that they are superimposed on one another. Two cylindrical weights are placed at the areas marked with an "x" (FIG. 3) so that a 0.836 pound per square inch weight is applied to the 3".times.6" portion of test sample 60 located on the raised platform 70, (less the area under cylinder 64). The total weight applied is approximately 12.4 pounds (5623 grams).

Sixty milliliters of a 0.87 percent aqueous saline solution commercially available from Baxter Scientific under the trade designation Blood Bank Saline is poured through funnel 72 in cylinder 64 so as to reach test sample 60. The time required for the 60 milliliter saline solution to disappear from the surface of the test sample 60 is recorded. After the fluid disappears from the surface of the test sample, the blotter strips are removed and weighed to determine the amount of liquid absorbed by the blotter strips. New blotter strips are weighed and placed next to the test sample and a second 60 milliliter insult is applied through the funnel 10 minutes after the first insult was applied. Again, the time required for the fluid to disappear from the surface of the test sample is recorded. The blotter strips are removed and weighed to determine the amount of liquid absorbed by the blotter strips. The procedure of replacing the blotter strips with new strips, insulting the test sample with 60 milliliters of Blood Bank Saline, determining the amount of time necessary for the fluid to disappear from the surface of the test sample 60 and determining the amount of liquid absorbed by the blotter strips is repeated for a total of 5 insults. Each insult

occurs 10 minutes after the prior insult. The amount of leakage for each insult is determined by subtracting the dry blotter weights from the wet blotter weights for the blotter strips used for that insult. The intake rate for each insult is determined by subtracting the leakage from the 60 milliliter insult and dividing by the intake time $\times (60 \text{ ml} - \text{leakage}) / \text{intake time (min)}$

EXAMPLES

Example 1:

COMPARATIVE STUDY OF ABSORBENT ARTICLES

A comparative study was conducted on the absorbency of absorbent articles in accordance with an implementation of the present invention (Sample 1) and a representative conventional diaper (Pampers Baby Dry). The results of the study are displayed in Table 1 below:

TABLE 1

TESTED DIAPER	PRESSURE (PSI):	0.1	0.1	0.1	0.5	0.5	0.5
	DOSE:	1	2	3	1	2	3
Sample 1	Absorption Times (s)	2	2	2	2	3	5
Pampers Baby Dry	Absorption Times (s)	4	4	9	5	10	>600

The present invention has been described in connection with the preferred embodiments. These embodiments, however, are merely for example and the invention is not restricted thereto. Any examples described herein are illustrative of preferred embodiments of the inventive subject matter and are not to be construed as limiting the inventive subject matter thereto. It will be understood by those skilled in the art that other variations and modifications can easily be made within the scope of the invention as defined by the appended claims.